



PHOTO VIDEO EQUIPMENT

2010

FOMEX[®]



FOMEX® □ - Series



D 200



D 400



D 600



D 1000

Model	D200	D400	D600	D1000
AC Input	110 / 220V , 50/60 Hz			
Flash Output, Max	200Ws	400 Ws	600 Ws	1000 Ws
Tube Replacement	Detachable (Easy to replace)			
Color Temp.	5500k (±150k)			
Output Control Range	F2.8 ⁸ ~F22 ⁸ (6f-stops)	F5.6 ⁰ ~F45 ⁰ (6f-stops)	F5.6 ⁷ ~F45 ⁷ (6f-stops)	F8 ⁷ ~F64 ⁷ (6f-stops)
Power Control Knob	Volume Controller (VR)			
Recycle Time	0.1~1.2sec	0.2~1.8sec	0.3~2.7sec	0.3-2.4sec
Model Lamp	Halogen 250 W (E11 base , screw typed)			
Model Lamp Control	Volume Controller (VR)			
Ready Charged	Sound On : Buzzer and LED On / Sound Off : Model Lamp Blinks			
Over Temperature Warning	O.T (Red LED) Blinking, Warning Buzzer			
Synchro. Voltage	DC 8V			
Flash Trigger	Infrared Photo Cell, Synchro Cord, TEST Button			
Sound	ON / OFF			
Slave (Infrared Sensor)	ON / OFF			
Cooling Fan	DC Cooling Fan (Ball bearing typed)			
Dimension	23.5x14x17cm	28x14x17cm	28x14x17cm	35x14x17cm
Weight	2.35kg	2.5kg	2.7kg	3.4kg



Light weight & Strong Aluminum Housing, and Die-cast Connectors



FOMEX® HD - Series



HD 400



HD 600



HD 1000

Model	HD400	HD600	HD1000	H1000
AC Input		110/220V , 50/60 Hz		110/220 V AC
Flash Output, Max	400 Ws	600 Ws	1000 Ws	1000 Ws
Tube Replacement	Detachable (Easy to replace)			-
Color Temp.	5500k (±150k)			-
Output Control Range	F5.6 ⁰ ~F45 ⁰ (6f-stops)	F5.6 ⁷ ~F45 ⁷ (6f-stops)	F8 ⁷ ~F64 ⁷ (6f-stops)	-
Power Control Knob	Volume Controller (VR)			-
Recycle Time	0.2 ~ 1.8sec	0.3 ~ 2.7sec	0.3 ~ 2.4sec	-
Model Lamp	Halogen 1000 W (GX 6.35 base. 2-pin typed)			1000 W (GX 3.35 base. 2-pin)
Model Lamp Control	Volume Controller (VR)			Analog Control Volume (VR)
Ready Charged	Sound On : Buzzer and LED On / Sound Off : Model Lamp Blinks			-
Over Temperature Warning	O.T (Red LED) Blinking, Warning Buzzer			-
Syncho. Voltage	DC 8V			-
Flash Trigger	Infrared Photo Cell, Syncho Cord, TEST Button			-
Sound	ON / OFF			-
Slave (Infrared Sensor)	ON / OFF			-
Cooling Fan	DC Cooling Fan (Ball bearing typed)			DC Cooling Fan
Dimension	28x14x17cm	28x14x17cm	35x14x17cm	25x14x17cm
Weight	2.5kg	2.7kg	3.4kg	1.5kg

Reflectors



DR16
ø 16cm



DR18
ø 18cm



DR31
ø 31cm



DR43
ø 43cm



SR55
ø 55cm / Soft Reflector
silver/white

FOMEX® H - Light (Quartz)



H 1000



CSD
Concial Snoot



BARD
Backlight Reflector



SR70
ø 70cm / Soft Reflector
silver/white



PDD1
Pyrex Dome



PDD2
Pyrex Dome



PCD
Protect Cap

CRICKET - Series



C200



C300



C400

Item	C200	C300	C400
Flash Output , Max.	200 Ws	300 Ws	400 Ws
Output Control Range	F4.0~F32 (6f-stops)	F4.5~F32.5 (6f-stops)	F5.6~F45 (6f-stops)
Power Control	Power Variator, Continuous from 1 to 10		
Flash Tube Replacement	Detachable (Easy to replace.)		
Model Lamp	Krypton 100W		
Model Lamp Mode	Independent		
Model Lamp Dump	ON / OFF		
Color Temperature	5500K (±150K)		
Audible Beep	ON / OFF		
Ultra-Sensitive Photocell	ON / OFF		
Recycle Time	0.2~1.0sec	0.3~1.4sec	0.4~1.8sec
Cooling Fan	DC Cooling Fan		
Overheat Alarm and Lamp	Buzzer alarm and Red LED Light		
Housing Material	PC ABS		
Dimension	26x12x8cm (with Standard Reflector)		
Weight	1.4kg	1.5kg	1.6kg

Reflectors for CRICKET



CR13
13cm



CR16
16cm



CR18
18cm



PCC
Protect Cap

Accessories



BD18
Barn Doors



ZS1224
Zoomspot



CF7
Colour Filter set



Honeycomb for DR31
20°/40°



Honeycomb for CR18/DR18
10°/20°/30°/40°



HL - E11
Model Lamp
250w / D



HL - GX6.35
Model Lamp
1000w / H & HD



KL - E26
Model Lamp
100w / Cricket



Flash Tubes



Dr.RAY
SMART RADIO SLAVE

1010200



Hot shoe PC Sync

1010301

1010302



1010270
5.5 SYNC Cable



EC-21
Power Cable

Soft Boxes



RECTA



STRIP



QUADRA



OCTA



GRID

30x60cm

40x60cm

40x70cm

50x70cm

60x80cm

60x90cm

75x100cm

80x100cm

80x120cm

90x120cm

100x140cm

120x180cm

30x90cm

30x120cm

40x120cm

75x175cm

45x45cm

70x70cm

100x100cm

∅ 90cm

∅ 120cm

∅ 150cm



The Patented Article

Speed Rings for Soft Box



Fomex D



Cricket



MutiblitZ



Broncolor



Elinchrom



Hensel



Balcar



Comet



Photogenic



Speedotron



Sunstar

Umbrellas



UMW85/101/152
White
∅ 85/101/152cm



UMS85/101
Silver
∅ 85/101cm



UMG85/101/152
Gold
∅ 85/101/152cm



UMT85/101
Translucent
∅ 85/101cm



UMB85/101
Brolly Boxes
∅ 85/101cm

Reflectors (Light Disc)



RSW56/80/110
Silver/White
∅ 56/80/110cm



RG56/80/110
Gold/Silver
∅ 56/80/110cm



RDF56/80/110
Diffuser
∅ 56/80/110cm



RTSW80
Silver/White
∅ 80cm

Carrying Bags (Studio Kit)



SLB2H
40x25x40cm



SLB3H
58x25x40cm



SLBLS
Light Stands Carrying Bag
110x20x24cm



Sand Bag



2-in-one



RGB152
Backdrop Panels
Gray/Blue
150x200cm

Flag Panels



4-in-one

FP1824
Silver/White/Gold/Black
46x61cm



4-in-one

FP2430
Silver/White/Gold/Black
61x76cm



4-in-one

FP3036
Silver/White/Gold/Black
76x91cm



Light Sheds
LS40 40x40x40cm
LS60 60x60x60cm
LS120 120x120x120cm



Light tent
LT40 40x40x40cm
LT60 60x60x60cm

No Flicker Ultra-long Lifetime Eco-friendly Lamp

FOMEX® N Light

Brand New, Sensational Lighting Device,
we suggest you to enjoy

- No flickering light provides higher Color-Rendering, nearer to Natural Lights
- Incredible Lamp Life, over than 11 Years (100,000 Hours) long
- Green Environmental Friendly Lamp (contained Mercury Below 3 mg)



N100



N200



N300

Item	N100	N200	N300
Head size (W x L x H)		325 x 140 x 170 mm	
Head weight	2.38 kg	2.64 kg	2.70 kg
Lamp size	dia. 240mm / H: 180mm	dia. 345mm / H: 180mm	dia. 425mm - H: 185mm
Lamp weight	0.82 kg	1.18 kg	1.30 kg
Reflector available	DR31 (dia. 340mm)	DR43 (dia. 440mm)	SR55 (dia. 550mm)

DTW -Series

Having efficient optics system, DTW series's fresnel lens are specially designed and expressed softer lighting as well as widely diffused the focusing range form a single point focus to wider angle. As the body of moldule structure is made with incorrodible aluminum's extrusion mouldling and used the light weight die-casting having perfect persistence, so there's no difficulty to use in nasty weather, the light focusing can be changed by moving lamp position and the circular mirror makes the lighting uniformly and perfectly diffusible. Bracket can be usable the adaptor 5/8" or 1-1/8"(29mm).



DTW150



DTW300



DTW650



DTW1000



DTW2000

HQI / DTD -Series

It's essential for fresnel daylight to be compact size, and high efficient and light weight, DTD-1200 compact daylight is the best choice. Fresnel lens are specially designed and expressed softer lighting as well as widely diffused the focusing range from a single point focus to wider angle. As the body of moldule structure is made with incorrodible aluminum's extrusion mouldling and used the light weight die-casting having perfect persistence, so there's no difficulty to use in nasty weather. The light focusing can be changed by moving lamp position and the circular mirror makes the lighting uniformly and perfectly diffusible. Bracket can be usable the adaptor 5/8" or 1-1/8"(29mm).



HQI150



DTD1200



The electronic ballast with remote booster control which is multi voltage can be used for various lighting accessories, and flicker free. it makes possible for speed of shutter into 10000/sec frame, and colour temperature is uniformly preserved.

Fluorescent Light

In the field of photography, imaging & broadcasting, fluorescent lighting system is suitable the source of light for working digital image which is soft and cool lighting quality. Only exchanging the fluorescent lamps, the tungsten(3,100K) and daylight(5,300K) is convertible, refers to the condition of photography, it can be mixed up with studio flash lighting, HMI and tungsten lighting. Compared with the same light output range, approx. 2.5 times brighter, little electricity consumption and more than 8000 hours long life are strong points. Due to low heat of the fluorescent lamp, it's highly adaptable for close up shooting. And it provides uniformly diffused lighting in the wider space.



DSR 2x



DSR 4x



DSR 6x

Halogen / Tungsten Light

Halogen lighting is the ideal for the field production and fast turnaround location use. it can be used not only digital and analogue photography but video photography and possibility of using various accessories. And it's kept stabilized life and fixed colour temperature and preserved the expression of lighting.



DTR150



DTR800



DTR2000

Light Stands



H629 H630 H600 H607
Air Cushioned H304 H303

YH629	37.5cm	87.5cm	35cm	0.64kg	1.5kg
YH630	58cm	200cm	57cm	1.15kg	1.5kg
YH600	88cm	250cm	86cm	1.05kg	5kg
YH607	110cm	290cm	108cm	2kg	10kg



H560 Caster Wheel Set Set of three EX36 EX90 Gun Stand EX35 Boom Stand 35 EX30 Boom Stand 30



CST19 C-Stand 19 CST24 C-Stand 24 CST29 C-Stand 29



Grip Head



Grip Head Double

CST29	135cm	135cm	310cm	95cm	7kg	10kg
CST24	124cm	124cm	296cm	95cm	6kg	10kg
CST19	80cm	80cm	127cm	95cm	5kg	9kg



Grip Arm

Accessories



EX113
Spigot



EX119
Spigot



EX114
16mm Adapter



EX152
Female Adapter



EX213
Extension Bar



EX336
Pivoting Clamp



EX335
Super Clamp



EX276
U-Hooks



EX259
Single Hooks



EX241
L-Brackets



EX235
Narrow Hooks



EX242
Extension Arm



EX237
Flex Arm



EX401
Wall Plate



EX405
Female Plate



EX601
Locking Knob



EX501
Single Hooks



EX505
Expan



V8510
Background Supports



FOMEX, a world wide leader of Lighting System Industry, has continued research and development on the innovation for new lighting technology.

'Nearer to the Nature, Closer to Humanity'

That is the main issue of FOMEX, trying to provide Better Qualification and More Comforts for every customer.

We wish that our high Technology applied on our products would bring you More Convenient Operating and Enough Satisfaction.

Your kind feedback on our products also would be much helpful to us all.

FOMEX[®]

Head Office.....
515-11 Shinsa-Dong Kangnam-Gu Seoul Korea
Tel +82 2 511 9904 Fax +82 2 511 9906
<http://www.fomex.com> E-mail fomex@fomex.com